

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE  
ATTENTION: OFFICE OF PETITIONS

In Re Application of:  
Samir Soliman

Serial No.: 10/672,824  
Filed: April 26, 2004

For: WIRELESS COORDINATION AND  
MANAGEMENT SYSTEM

Group Art Unit: 3662

Attention: Office of Petitions  
Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

**PETITION TO DEFER ISSUE**

UNDER 37 C.F.R. 1.314

PENDING CONSIDERATION OF PETITIONS REGARDING CORRECTION TO  
PRIORITY AND FILING DATE OF ABOVE APPLICATION

Dear Sir/Madam:

Applicant hereby submits this Petition pursuant to 37 C.F.R. 1.314 requesting that the above-identified patent application be **DEFERRED FROM ISSUANCE** until such time as three (3) corresponding Petitions attached hereto are decided, the first regarding the filing date of the above-identified Patent Application No. 10/672,824 ("Continuation Application"); the second regarding the date of abandonment of the priority Patent Application No. 10/011,965 ("Parent Application"); and the third being a Petition for Extension of Time of 3 months in which to respond to the first Office Action in the Parent Application. The issues explained in these Petitions were only recently discovered.

I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail in an envelope addressed to the Commissioner of Patents and Trademarks, Alexandria, VA 22313, on:

December 21, 2005

(Date of Deposit)

Victoria J. Pacey

(Name of Person Making Deposit)

(Signature)

12/30/2005 SLUANG1 00000011 170026 10672824  
01 FC:1464 130.00 DA


Applicant believes that *extraordinary* circumstances merit deferral from issue of the Continuation Application, as explained in the attached Petitions, until such Petitions are decided.

Please charge the deposit account for the petition fee (\$130.00) pursuant to 37 C.F.R. 1.17(h). Please charge Deposit Account No. 17-0026 for any shortage in fees in connection with this petition.

Applicant respectfully requests grant of this Petition to Defer from Issue.

Dated: December 21, 2005

Respectfully submitted,

By:   
Andrea L. Mays  
Attorney for Applicant  
Registration No. 43,721

QUALCOMM Incorporated  
5775 Morehouse Drive  
San Diego, California 92121-2779  
Telephone: (858) 651-8546  
Facsimile: (858) 658-2502

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

ATTENTION: OFFICE OF PETITIONS

In Re Application of  
Samir Soliman

Serial No.: 10/672,824

Filed: April 26, 2004

For: WIRELESS COORDINATION AND  
MANAGEMENT SYSTEM

Group Art Unit: 3662

Attention: Office of Petitions  
Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

**PETITION TO ACCORD FILING DATE**

PURSUANT TO 37 C.F.R. 1.53(b) and 37 C.F.R. 1.57(a)

Dear Sir/Madam:

Applicant hereby submits this Petition pursuant to 37 C.F.R. 1.53(b) and 37 C.F.R. 1.57(a) requesting that the filing date of the above-identified Patent Application No. 10/672,824 ("Continuation Application") be corrected to the original application filing date of September 26, 2003.

I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail in an envelope addressed to the Commissioner of Patents and Trademarks, Alexandria, VA 22313, on:

December 21, 2005

(Date of Deposit)

Victoria J. Pacey

(Name of Person Making Deposit)

(Signature)

Prosecution History

Patent Application No. 10/011,965 ("Parent Application") was filed on November 5, 2001. The above-identified Continuation Application was filed on September 26, 2003 claiming priority to the Parent Application. After filing the Continuation Application, Applicant received a Notice of Missing Parts dated March 31, 2004 for the omission of the oath and declaration as well as an inadvertent omission of Figure 1. Applicant timely responded on April 23, 2004 with the declaration, power of attorney, copy of Figure 1, and the associated fee. The Filing Receipt of March 31, 2004 indicated a filing date of September 26, 2003. On May 6, 2004, however, the Patent Office mailed a Corrected Filing Receipt indicating a filing date of April 26, 2004. It is Applicant's contention that Applicant is entitled to a filing date of September 26, 2003, not April 26, 2004.

Request for Correction to the Filing Date

Applicant respectfully requests correction to the earlier filing date of September 26, 2003 for the Continuation Application. Figure 1 was in fact not omitted upon filing the Continuation Application because it was incorporated by reference from the Parent Application. 37 C.R.F. 1.57(a) states that:

(a) Subject to the conditions and requirements of this paragraph, if all or a portion of the specification or drawing(s) is inadvertently omitted from an application, but the application contains a claim under § 1.55 for priority of a prior-filed foreign application, or a claim under § 1.78 for the benefit of a prior-filed provisional, nonprovisional, or international application, that was present on the filing date of the application, and the inadvertently omitted portion of the specification or drawing(s) is completely contained in the prior-filed application, the claim under § 1.55 or § 1.78 shall also be considered an incorporation by reference of the prior-filed application as to the inadvertently omitted portion of the specification or drawing(s).

Applicant corrected the omission of Figure 1 in the Continuation Application by timely responding to the Notice of Missing Parts on April 23, 2004 with the declaration, power of attorney, and copy of Figure 1. Figure 1 of the Parent Application is identical to Figure 1 of the Continuation Application. A copy of the Parent Application as filed is

attached hereto. Applicant respectfully contends that Figure 1 was incorporated by reference from the Parent Application into the Continuation Application when Applicant made the priority claim to the Parent Application upon filing. At the time of filing the Continuation Application, Applicant had no idea that the Parent Application had in fact been technically abandoned earlier than thought. (See associated Petition to Correct Date of Abandonment of the Parent Application.)

Alternatively, and in the event that the Director does not grant the Petition to Correct Date of Abandonment of the Parent Application, Applicant contends that Figure 1 is not necessary for an understanding of the subject matter sought to be patented (37 C.F.R. 1.81(a)) and was thus not necessary for obtaining the filing date of September 26, 2003. Figure 1 provides an overview of various pre-existing devices of a communications environment in which the invention operates. Additionally, the components of Figure 1 are clearly described in the description section of the specification, and the addition of Figure 1 after the filing date of September 26, 2003 in no way constituted new matter. Had Figure 1 been omitted altogether and the components therein described solely in the text of the application, the application would have been entirely enabled.

The discrepancy in the filing date for the Continuation Application was found very recently upon review of the file after having received the Notice of Allowance.

Correction of the filing date to the earlier September 26, 2003 is very important for two (2) reasons: 1) to preserve the priority claim in the Continuation Application to the Parent Application of November 5, 2001; and 2) to at least obtain the filing date of September 26, 2003 instead of April 26, 2004 in the event that the associated Petition to Correct Date of Abandonment of the Parent Application is not granted.


Applicant recognizes its error in not pointing out the discrepancy in the filing date earlier and takes this error very seriously. Applicant respectfully requests that the earlier filing date of September 26, 2003 be accorded the Continuation Application.

Please charge the Deposit Account for the petition fee (\$400.00) pursuant to 37 C.F.R. 1.17(f). Please charge Deposit Account No. 17-0026 for any shortage in fees in connection with this petition.

Dated: December 21, 2005

Respectfully submitted,

By:



Andrea L. Mays  
Attorney for Applicant  
Registration No. 43,721

QUALCOMM Incorporated  
5775 Morehouse Drive  
San Diego, California 92121-2779  
Telephone: (858) 651-8546  
Facsimile: (858) 658-2502

## PART B - FEE(S) TRANSMITTAL

Complete and send this form, together with applicable fee(s), to: **Mail** Mail Stop ISSUE FEE  
 Commissioner for Patents  
 P.O. Box 1450  
 Alexandria, Virginia 22313-1450  
 or **Fax** (571) 273-2885

INSTRUCTIONS: This form should be used for transmitting the ISSUE FEE and PUBLICATION FEE (if required). Blocks 1 through 5 should be completed where appropriate. All further correspondence including the Patent, advance orders and notification of maintenance fees will be mailed to the current correspondence address indicated unless corrected below or directed otherwise in Block 1, by (a) specifying a new correspondence address; and/or (b) indicating a separate "FEE ADDRESS" maintenance fee notifications.

CURRENT CORRESPONDENCE ADDRESS (Note: Use Block 1 for any change of address)

23696 7590 08/26/2005

Qualcomm Incorporated  
 Patents Department  
 5775 Morehouse Drive  
 San Diego, CA 92121-1714



Note: A certificate of mailing can only be used for domestic mailings of Fee(s) Transmittal. This certificate cannot be used for any other accompanying papers. Each additional paper, such as an assignment or formal drawing, must have its own certificate of mailing or transmission.

## Certificate of Mailing or Transmission

I hereby certify that this Fee(s) Transmittal is being deposited with the United States Postal Service with sufficient postage for first class mail in an envelope addressed to the Mail Stop ISSUE FEE address above, or being facsimile transmitted to the USPTO (571) 273-2885, on the date indicated below.

VICTORIA PACBY	(Depositor's name)
<i>Victoria Pacby</i>	(Signature)
11/9/05	(Date)

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/672,824	04/26/2004	Samir S. Soliman	010124C1	8905

TITLE OF INVENTION: WIRELESS COORDINATION AND MANAGEMENT SYSTEM

APPLN. TYPE	SMALL ENTITY	ISSUE FEE	PUBLICATION FEE	TOTAL FEE(S) DUE	DATE DUE
nonprovisional	NO	\$1400	\$300	\$1700	11/28/2005

EXAMINER	ART UNIT	CLASS-SUBCLASS
ISSING, GREGORY C	3662	342-357130

1. Change of correspondence address or indication of "Fee Address" (37 CFR 1.363).

- ☐ Change of correspondence address (or Change of Correspondence Address form PTO/SB/122) attached.  
☐ "Fee Address" indication (or "Fee Address" Indication form PTO/SB/47; Rev 03-02 or more recent) attached. Use of a Customer Number is required.

2. For printing on the patent front page, list

- (1) the names of up to 3 registered patent attorneys or agents OR, alternatively,  
 (2) the name of a single firm (having as a member a registered attorney or agent) and the names of up to 2 registered patent attorneys or agents. If no name is listed, no name will be printed.

1. PHILIP WADSWORTH  
 2. BRUCE W. GREENHAUS  
 3. ANDREA L. MAYS

3. ASSIGNEE NAME AND RESIDENCE DATA TO BE PRINTED ON THE PATENT (print or type)

PLEASE NOTE: Unless an assignee is identified below, no assignee data will appear on the patent. If an assignee is identified below, the document has been filed for recordation as set forth in 37 CFR 3.11. Completion of this form is NOT a substitute for filing an assignment.

(A) NAME OF ASSIGNEE

(B) RESIDENCE: (CITY and STATE OR COUNTRY)

QUALCOMM INCORPORATED

SAN DIEGO, CALIFORNIA

Please check the appropriate assignee category or categories (will not be printed on the patent): ☐ Individual ☒ Corporation or other private group entity ☐ Government

4a. The following fee(s) are enclosed:

- ☒ Issue Fee  
☐ Publication Fee (No small entity discount permitted)  
☐ Advance Order - # of Copies \_\_\_\_\_

4b. Payment of Fee(s):

- ☐ A check in the amount of the fee(s) is enclosed.  
☐ Payment by credit card. Form PTO-2038 is attached.  
☒ The Director is hereby authorized by charge the required fee(s), or credit any overpayment Deposit Account Number 17-0026 (enclose an extra copy of this form).

5. Change in Entity Status (from status indicated above)

- ☐ a. Applicant claims SMALL ENTITY status. See 37 CFR 1.27. ☐ b. Applicant is no longer claiming SMALL ENTITY status. See 37 CFR 1.27(g)(2).


The Director of the USPTO is requested to apply the Issue Fee and Publication Fee (if any) or to re-apply any previously paid issue fee to the application identified above. NOTE: The Issue Fee and Publication Fee (if required) will not be accepted from anyone other than the applicant; a registered attorney or agent; or the assignee or other part interest as shown by the records of the United States Patent and Trademark Office.

Authorized Signature *Andrea L. Mays*  
 Typed or printed name ANDREA L. MAYS

Date 11/9/05  
 Registration No. 43,721

This collection of information is required by 37 CFR 1.311. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, Virginia 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 14 Alexandria, Virginia 22313-1450.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.



5775 Morehouse Drive,  
San Diego, California 92121-2779  
(858) 587-1121 Fax: (858) 658-2502

## *Facsimile Transmittal*

**DATE:** November 9, 2005

**TO:** Mail Stop Issue Fee; USPTO  
Docket No. 010124C1

**FAX :** 571 273 2885

**FROM:** Andrea L. Mays

**PHONE:** (858) 651-8546

**FAX** (858) 658-2502

**Number of Pages including this cover sheet:** 3

**THIS MESSAGE IS INTENDED ONLY FOR THE USE OF THE INDIVIDUAL TO WHOM IT IS ADDRESSED AND CONTAINS INFORMATION THAT IS PRIVATE AND/OR PROPRIETARY. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this communication in error, please notify us immediately. Thank you!**



Confirmation Report - Memory Send

Time : Nov-09-2005 03:20pm  
Tel line : +  
Name : 8588456880

Job number : 538  
Date : Nov-09 03:19pm  
To : 915712732885  
Document pages : 003  
Start time : Nov-09 03:19pm  
End time : Nov-09 03:20pm  
Pages sent : 003  
Status : OK



COPY

Job number : 538

\*\*\* SEND SUCCESSFUL \*\*\*

**QUALCOMM**

5775 Morehouse Drive,  
San Diego, California 92121-2779  
(858) 587-1121 Fax: (858) 658-2502

***Facsimile Transmittal***

**DATE:** November 9, 2005  
**TO:** Mail Stop Issue Fee; USPTO  
Docket No. 010124C1  
**FAX :** 571 273 2885  
**FROM:** Andrea L. Mays  
**PHONE:** (858) 651-8546  
**FAX** (858) 658-2502

**Number of Pages including this cover sheet: 3**

THIS MESSAGE IS INTENDED ONLY FOR THE USE OF THE INDIVIDUAL TO WHOM IT IS ADDRESSED AND CONTAINS INFORMATION THAT IS PRIVATE AND/OR PROPRIETARY. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this communication in error, please notify us immediately. Thank you!

**WIRELESS COORDINATION AND MANAGEMENT SYSTEM****BACKGROUND OF THE INVENTION****5 1. Related Applications**

[0001] This application claims priority to U.S. Provisional Application No. 60/316,363, filed August 30, 2001.

**2. Field of the Invention**

10 [0002] This invention relates generally to information and communication systems and, more particularly, to a wireless communication system for coordinating information and for providing notifications to a user regarding the information.

**3. Description of the Related Art**

15 [0003] The explosive growth of computers and the Internet has resulted in a vast wealth of information being available to individuals. This has coincided with an increased mobility and pace in everyday life, so that a person can become overwhelmed by an increasing load of information, as well as an increasing number of things to do and places to go. As a result, the ability to efficiently and competently maintain and manage  
20 information and tasks can provide a person with a significant edge in society.

[0004] There currently exists a variety of devices for storing and managing information such as calendars, to-do lists, and contact lists. The types of devices that can be used to store and manage such information vary widely and include desktop and laptop computers, as well as wireless mobile devices, such as personal digital assistants and  
25 mobile telephones. The upside of having so many available devices is that a person has several ways to store information and retrieve information.

[0005] However, the downside is that the sheer number of devices ends up adding to the confusion rather than making life easier. It is common for a single person to own a personal computer, a mobile phone, and a personal digital assistant and to use each of the  
30 devices to store information. This makes it difficult for a person to keep track of the

devices, much less keep track of the information. The problem is even getting worse, as other devices, such as televisions and household appliances, are being equipped with the ability to store information. Coordination of information among the different devices can be a problem.

5 [0006] Another problem is that the devices are passive in that they are generally configured to just store information. For example, a device that is used to store a grocery list generally relies on the user to initiate periodic review of the list and to update the list as items are purchased or as the items need to be added. Thus, the device relies on user initiative in order to be truly helpful. As a result, the users who need the most help –  
10 those users who generally need to be reminded to review items on the list – are those who would benefit the least from having such a device.

[0007] In view of the foregoing, there is a need for an efficient way of coordinating and managing information among different devices, as well as a way of assisting users in utilizing such information.

15

## SUMMARY OF THE INVENTION

[0008] In accordance with the invention, information that is received from one or more users over a communication network is managed even while the user location changes. A  
20 user provides information to be managed using any suitable data device communicating with a network node, such as a data acquisition device that is a wireless, mobile communication device. The user's location within a communication environment is monitored and an alarm is sent to a user when the user is near a location that satisfies user-specified criteria. The user-provided information is stored at a central database that  
25 is linked to the communication network. When an authorized user revises the information, any other authorized user can access the revised information by accessing the central database through a node of the communication network. Thus, user information may be efficiently managed across different devices and user locations.

[0009] The provided information may comprise a list of items that are needed by the user,  
30 such as a grocery list, a gift list, or a food list. The location of the user in the communication environment is tracked by monitoring the location of the data acquisition device, which can be a mobile phone that is carried by the user. A message is sent to the

mobile phone when the user is at or near a location where the user can obtain an item from the list of items needed. For example, when the user is near a store that sells an item on the user's grocery list, a notification is sent to the user regarding the user's proximity to the store and reminding the user that the store sells an item on the grocery list.

- 5 [0010] Other features and advantages of the present invention should be apparent from the following description of the preferred embodiment, which illustrates, by way of example, the principles of the invention.

### BRIEF DESCRIPTION OF THE DRAWINGS

10

[0011] Figure 1 is a block diagram of a communication environment in which are disposed several nodes of a communication network.

[0012] Figure 2 is a block diagram of some of the nodes of the communication network.

- 15 [0013] Figure 3 is a flow diagram that illustrates the operations performed in obtaining and coordinating data among the nodes of the communication network.

[0014] Figure 4 is an illustration of an exemplary data structure.

[0015] Figure 5 is another illustration of an exemplary data structure.

[0016] Figure 6 is another illustration of an exemplary data structure.

- 20 [0017] Figure 7 is a flow diagram that illustrates the operations performed in notifying a user when the user is near a location that meets criteria specified in data of the communication network.

[0018] Figure 8 is a block diagram of a communication environment that includes a remote communication device and a retail establishment.

- 25 [0019] Figure 9 is a block diagram of a device comprised of a node of the communication network illustrated in Figure 1, illustrating the hardware components.

[0020] Figure 10 is a block diagram of a device that comprises a wireless node of the communication network illustrated in Figure 1, illustrating the hardware components.

### DETAILED DESCRIPTION

30

[0021] In accordance with the invention, a variety of network communication devices communicate over a network and are housed in various host systems or locations, thereby

comprising nodes of a network. Figure 1 is a block diagram of a communication environment 100 in which are disposed several nodes of a communication network 102 (shown in Figure 2), including a data acquisition device 110, service manager 115, retail establishment 120, and extraterrestrial global positioning system (GPS) satellites 130. A wide variety of other devices may be communicatively linked to the communication network 102 via host systems. For example, an automobile 137 may host a communication device 135 and an appliance 140 may host a communication device 135, as described further below. Thus, the satellites 130, data acquisition device 110, retail establishment 120, and various communication devices 135 communicate with each other over the communication network 102 and comprise nodes of the network.

[0022] For clarity of illustration, Figure 1 schematically shows the communication devices 135 as being externally attached to their respective host systems, although it should be appreciated that the communication devices 135 may be coupled to their respective host systems in a wide variety of ways. Furthermore, although Figure 1 only shows a single instance of some nodes such as a single appliance and a single automobile, the communication environment 100 can include multiple instances of each node.

[0023] The disclosed system manages the provision and access of information between two or more nodes of the communication network 102. The service manager 115 monitors a user's location within the communication environment 100 and sends update messages to the user when the user's location is near a location that satisfies user-specified criteria. The user can provide information to be managed using any of the nodes of the communication network 102. The service manager 115 also stores the information at a central database that is linked to the communication network 102, as described in further detail below.

[0024] The data acquisition device 110 is a remote, wireless communication device that is capable of communicating with the service manager 115 over the network 102. The data acquisition device 110 is preferably a hand-held mobile computer device, such as wireless telephone or a personal digital assistant. The data acquisition device 110 is configured to receive data from the user. The data acquisition device 110 can upload the received data to the communication network 102 for storage at a central database.

[0025] The data acquisition device 110 is preferably movable throughout the communication environment 100 such that the location of the data acquisition device 110

can change with respect to the location of any of the nodes. The GPS satellites 130 can be used to determine the location of the data acquisition device 110 within the communication environment 100, as well as the location of other objects within the communication environment, as described below.

5 [0026] The service manager 115 is any device that is capable of sending and receiving data transmissions to and from the data acquisition device 110 or any of the other nodes of the network 102. The service manager performs the data management functions, as described further below. The service manager 115 may be operated by a service provider that provides services according to the methods described herein. For example, the  
10 service manager 115 may be operated by a telephone company that provides wired or wireless telephone and other network services to the nodes of the communication network. The service manager 115 may also be operated by an Internet service provider.

[0027] The communication device 135 is a device that is configured to establish a communication link with the network 102 for the exchange of data, such as through a  
15 wired or wireless modem. A communication device 135 can communicate with the network 102 using any of a wide variety of communication protocols. Preferably, the communication device 135 includes a user interface and memory that enables a user to input and store data, as described below.

[0028] As mentioned, the communication device 135 can be coupled to any of a wide  
20 variety of host devices to thereby render the host device a node of the communication network 102. The communication device 135 is configured to receive data from the user. The communication device 135 can establish a connection with the network 102, such as a wireless or wired connection, and upload received data to the network 102. The communication device 135 differs from the data acquisition device 110 in that the  
25 communication device 135 resides with and is associated with a host device, such as an automobile or an appliance. On the other hand, the data acquisition device 110 is an independent handheld communication device, such as a mobile phone or personal digital assistant.

[0029] Figure 1 shows a first communication device 135 coupled to an automobile 137  
30 and a second communication device 135 coupled to an appliance 140. In this manner, the automobile 137 and appliance 140 are effectively rendered nodes of the communication network 102. An appliance 140 is any instrument that is configured to perform a task or

function or assist the user in performing a task or function. An appliance 140 can comprise a common household appliance or office appliance, such as, for example, a refrigerator, washer, dryer, personal computer, etc.

5 [0030] A retail communication device 150 is a communication device 135 that is coupled to the retail establishment 120 to thereby communicatively link the retail establishment 120 to the network 102. The retail communication device 150 is a computing device that is configured to transmit data over the communication network 102 and receive data from the communication network 102. The retail communication device 150 can also receive data from a user. The retail communication device 150 is preferably fixedly located at the  
10 retail establishment 120. The retail communication device 150 may have the same construction as the communication device 135 or may have additional components that are particularly suited for use in the retail establishment.

[0031] The retail establishment 120 is representative of any entity or party that provides goods and/or services within the communication environment 100, whether or not for  
15 monetary compensation. The retail establishment 120 includes any type of goods or service provider as well as the structure in which such a provider is located. Thus, the retail establishment 120 can include a grocery store, a convenience store, a restaurant, a gas station, or any other type of store. Typically, the retail establishment 120 is disposed at a stationary location within the communication environment 100, although the retail  
20 establishment 120 may also be mobile.

[0032] Figure 2 is a block diagram that illustrates nodes comprised of various devices that are communicatively linked to the communication network 102, including the data acquisition device 110, retail communication device 150, service manager 115, and communication device 135. Each of the devices are preferably configured to store and  
25 retrieve data within internal memory according to well-known devices and methods. Figure 2 shows only a single communication device 135 linked to the network 102. However, the network 102 may include several communication devices 135, each of which is coupled to a respective host device, such as an automobile 137 or an appliance 140, as shown in Figure 1.

30 [0033] The communication network 102 can be one or more terrestrial or extraterrestrial networks configured to transport data, as well as a combination of terrestrial and extraterrestrial networks. The communication network 102 can include a common or

private telecommunications network such as a public switched telephone network (PSTN), a local area network (LAN), a wide area network (WAN), a cable-based telecommunication network, a cellular network, a Personal Communications System (PCS), an extraterrestrial satellite system, as well as combinations thereof or any other  
5 wired and/or wireless means of transporting data. The communication network 102 may be coupled with or overlaid by a TCP/IP network, such as the Internet or an intranet.

[0034] The data acquisition device 110 generally communicates with the network 102 by establishing a wireless connection with a gateway 202, which is communicatively linked to the communication network 102. The gateway 202 may be a base station or a cell of  
10 the type associated with mobile phone services. The gateway 202 may also be some other type of wireless connection through which the data acquisition device 110 can gain access to the communication network 102. The gateway may be operated by a telephone service provider or an Internet service provider to thereby provide such services to the data acquisition device 110. There may be multiple gateways disposed throughout the  
15 communication environment 100.

[0035] The data acquisition device 110 can preferably also establish a direct communication link with any of the nodes, such as with the retail communication device 150 or communication device 135, as illustrated by the two-way connections 202 in  
20 Figure 2. In this regard, the communication devices 135 or 150 may be equipped with a docking station that enables the data acquisition device 110 to dock and exchange data with the communication device 135. The connection 202 may be wired or wireless according to any of a wide variety of communication protocols, including Bluetooth, IEEE 802.11x, UltraWideband, or any other communication protocol.

[0036] The communication device 135 and the retail communication device 150 may  
25 optionally both include a user interface 205 that allows a user to provide data, which can be stored locally in a respective data store 210. The user interface 205 can comprise any means of entering data, such as a keyboard or a mouse. The user interface 205 can also include software that is configured to assist a user in entering data. The communication device 135 and retail communication device 150 can also include display screens.

30 [0037] The retail communication device 150 can optionally be coupled to a printer 217 to allow a user to print out data that is accessed from the retail communication device 150. The retail communication device 150 can also be coupled to other peripheral devices that



are associated with the retail establishment 120, such as an automated teller machine (ATM) 219.

5 [0038] The service manager 115 includes applications that may be realized using software, hardware or combinations of software and hardware. The applications include a position locator 215 and an information manager 225. The service manager 115 also includes a server 220, which is software and/or hardware that enables the position locator 215 and information manager 225 to send and receive data to and from the nodes of the communication network 102. The position locator 215, server 220, and information manager 225 need not be incorporated into the service manager 115, but can rather reside  
10 at one or more separate nodes of the communication network 102 apart from the service manager 115. Thus, the position locator 215 and the information manager 225 can reside at separate locations or at the same network location. For example, the position locator 215 can reside in the data acquisition device 110 so that the data acquisition device can calculate its location and send information regarding its location to the service manager 115. The functionality of the position locator 215, information manager 225, and server 220 can also be incorporated into a single application executing at the same location.

[0039] The position locator 215 is configured to determine the location of the data acquisition device 110 using GPS information that is obtained from one or more of the GPS satellites 130 (Figure 1). The location of a device 110, 135 can be determined using  
20 any of a wide variety of methods and devices, such as according to the methods described in U.S. Patent No. 6,188,354, entitled "Method and Apparatus for Determining the Location of a Remote Station in a CDMA Communication Network" and U.S. Patent No. 6,081,229 entitled "System and Method for Determining the Position of a Wireless CDMA Transceiver," which are both incorporated herein by reference.

25 [0040] The information manager 225 is configured to store and maintain data received from any of the nodes of the communication network 102, such as from the data acquisition device 110, communication device 135, or retail communication device 150, as well as location data from the position locator 215. The information manager 225 can also transmit data and alarms to any of the nodes of the communication network 102.

30 [0041] The information manager 225 preferably maintains a data store 230 that functions as a central data repository for data access among nodes of the communication network 102. One or more users can establish an account with the service provider that operates

the information manager 225 to store and manage data in the data store 230 in exchange for a fee. For example, a telephone and/or Internet service provider may operate the information manager 225 and provide telephone services to a user (and access to the network 102) as well as services under the information manager 225. The information manager 225 may also be operated by an independent service provider that contracts with the operator of the gateway 202 to provide services to customers of the gateway operator.

**[0042] Data Management**

**[0043]** The data acquisition device 110 is configured to receive and store data provided directly by a user, such as through a keypad, or through a data port, such as a peer-to-peer connection to a data source. The communication device 135 and retail communication device 150 can also receive data directly from a user if they are equipped with a user interface such as a keypad or data port. When data is received, the device preferably transfers the data via the communication network 102 to the information manager 225, which stores the data in the central data store 230. The information manager 225 makes the data available to authorized users that have access to a node of the computer network 102. The information manager 225 dynamically updates the data in the data store 230 when an authorized user revises the data via a node of the communication network 102. This process is described in more detail with respect to Figure 3, which shows a flow diagram that describes the operations involved in obtaining and updating data.

**[0044]** In the first operation, represented by the flow diagram box numbered 310 in Figure 3, the user provides data either to the data acquisition device 110 or to another node of the communication network 102. In the case of the data acquisition device 110, the user preferably provides data using data entry means, such as an alphanumeric keypad on the data acquisition device 110. The data acquisition device 110 can also be equipped with voice recognition software or hardware for user entry of data. The data acquisition device 110 preferably is equipped with user interface software and a display that facilitates the entry of data. A user could also provide data to a node using a communication device 135 that is coupled to an appliance 140 or an automobile 137. A user can also provide data using a retail communication device 150. The respective device in which data was provided preferably stores the data in local memory.

**[0045]** The data provided by the user in the first operation 310 can be in any of a wide variety of formats and can relate to any of a wide variety of subjects, including to-do lists,

instructions, calendars appointments, reminders, notices, etc. In one embodiment, the user provides data to the data acquisition device 110 wherein the data comprises a list of items that the user desires to obtain, such as a grocery list, a gift list, or a food list. The list items preferably include at least one item that can be obtained at a retail establishment  
5 120 in the communication environment 100 (Figure 1).

[0046] With reference to Figure 4, the list can be stored as a data structure comprised of a table 410 that includes one or more elements 420, each element corresponding to an item in the list. Each element includes one or more data slots that contain data that is related to or descriptive of the corresponding item. The data slots can include, for example, item  
10 name, quantity of items needed, desired price, or any other information regarding the item. Preferably, there is also a data slot that contains the name of at least one retail establishment where the user prefers to obtain the item and/or a data slot that specifies one or more locations for the retail establishment. The retail establishment name and location can be specified using a code.

[0047] The table 410 is merely exemplary and it should be appreciated that the data structure could be in a different format or could include more or less of the data slots shown. For example, as shown in Figure 5, a data element might only include data slots for item name, quantity, retail establishment name, and retail establishment location. Alternately, as shown in Figure 6, a data element might only include data slots for item  
20 name, desired price range, and preferred retail establishment.

[0048] The data provided by the user in the first operation 310 may also comprise data provided using a communication device 135, such as data provided using the interface 205 (Figure 2). In this manner, the user can enter data directly into an appliance 140, automobile 137, or any other device that is coupled to a communication device 135. For  
25 example, the appliance 140 can be a refrigerator that has a communication device 135 with a data entry keypad located on the refrigerator door. The refrigerator, via the attached communication device 135, transfers user-provided data to the data acquisition device 110 or to the information manager 225 over the network 102. In another example the appliance 140 is a desktop computer into which the user enters data. The desktop  
30 computer can then transmit the data over the network 102 to the information manager 225 or directly to the data acquisition device 110.

[0049] The data provided by the user in the first operation 310 may also comprise data provided using the retail communication device 150. In this case, the user may be a representative of the retail establishment 120 or a customer of the retail establishment. The retail communication device 150 can be configured to receive and transmit data  
5 related to the retail establishment, such as data that relates to the name of the retail establishment, which can correspond to the name(s) in the lists shown in Figures 4-6. The data could also be descriptive of the location and operating hours of the retail establishment 120. The data can also be descriptive of items that are available at the retail establishment, such as item names, prices, discounts, quantity in inventory, etc.

10 [0050] With reference again to Figure 3, the next operation is represented by the flow diagram box numbered 315. In this operation, the node that received the data transmits the data to the information manager 225 over the network 102. For example, the data acquisition device 110, communication device 135, or retail communication device 150 may transmit received data to the information manager via the network 102. The data  
15 may be transmitted automatically when received. The data may also be transmitted when the user selects a "transmit" key. The data may also be transmitted upon occurrence of a predetermined event, such as whenever a predetermined time period elapses or when a device is powered on.

[0051] In the next operation, represented by the flow diagram box numbered 320, the  
20 information manager 225 stores the received data in the data store 230. The information manager 225 preferably maintains a list of access rights descriptive of users that are authorized to access the data. The access rights are preferably defined by a user when the user establishes an account with the information manager 225 and specifies other users that are to be granted access to data associated with the account. An account can be  
25 associated with one or more users, with each user having a set of access and revision rights related to data in the account. For example, the account may be associated with a family comprised of several users, with some of the users having access to all of the data and other users having access to only a subset of the data. A user can also specify that third parties, such as retail establishments, could have limited access to some of the data  
30 in the user's account.

[0052] In the next operation, represented by the flow diagram box numbered 330, the information manager makes the data available to authorized users. An authorized user

can preferably access the data using any of the nodes of the computer network 102, which are configured to download the data over the network 102. For example, the user can access the data using the data acquisition device 110 by causing the device 110 to connect to the network 102. When the user attempts to access a particular data structure, the data acquisition device 110 preferably establishes a connection with the information manager 225 and requests a copy of the data, such as a copy of a to-do list. Advantageously, any authorized user can access the data anywhere in the communication environment 100 using a data acquisition device 110 and by providing proper access validation, such as a username and password. When accessed, the user can view the data on a display screen or by printing a hard copy.

[0053] In the next operation, a user makes a revision to data in the user's account, as represented by the flow diagram box numbered 335. The revision can include any change to the data by an authorized user, such as the user adding a new item to a list or deleting an item from a list. When a revision is made, the data acquisition device 110 (or whatever node the user accessed to revise the data) notifies the information manager 225 of the revision. The information manager 225 then updates the corresponding data in the data store 230 accordingly, as represented by the flow diagram box numbered 340. In this manner, data revisions are dynamically reflected in the central data store 230, where the revised data may be accessed by authorized users.

[0054] Data revisions can also occur with respect to a retail establishment 120. A representative of a retail establishment 120 can revise retail establishment data, such as to update locations of retail establishments or to update data related to items that are available from the retail establishment.

[0055] In one embodiment, an appliance 140 is configured to make automatic adjustments to data based upon conditions related to the appliance. For example, if the appliance 140 is a refrigerator, the appliance can detect when certain refrigerated items are out of stock, such as if the refrigerator is out of eggs. The appliance can be equipped with a detector (such as a weight detector) that detects when eggs (or any other item) are present or when eggs are not present in an assigned location of the refrigerator. When a particular item is not present, the appliance 140 (via the communication device 135) can update the appropriate data in the user account, such as by adding an item to a grocery

list. A user of the data acquisition device 110 can access the updated data by accessing the central data store 230 using a node of the network 102.

[0056] The process shown in the diagram of Figure 3 enables a user or a group of users to provide and store data that is made available to authorized users. Revisions to the data are dynamically updated in the central data store 230, so that authorized users have access to the revisions anywhere in the communication environment as long as the user has access to a node of the communication network 102. This advantageously enables a user to use a plurality of devices to enter and retrieve data while the information manager 225 stores the data at the central data store and makes the data available to the different devices. In this manner, the devices have access to consistent data.

[0057] Notification Based on Proximity to Retail Establishment

[0058] As mentioned, a user can use the data acquisition device 110 to store information including a list of needed items, such as a grocery list. The communication system keeps track of the user's location within the communication environment and notifies the user when the user is near a location where the user can obtain an item on the list, such as when the user is near a retail establishment 120. This process is described with respect to the flow diagram shown in Figure 7.

[0059] In the first operation, represented by the flow diagram box numbered 710, the position locator 215 determines the location of the user by determining the location of the data acquisition device 110 and provides information regarding the location to the information manager 225. As mentioned, the user preferably carries the data acquisition device 110 at his or her side, so that the location of the data acquisition device 110 is effectively the same as the location of the user. The location of the data acquisition device 110 can be specified as an absolute position, such as a latitude and longitude. The location can also be specified as a relative position with respect to some object in the communication environment.

[0060] The position locator 215 can determine the location of the data acquisition device by coordinating with the data acquisition device 110, the GPS satellites 130 and the service manager 115 according to the systems and methods described in U.S. Patent No. 6,081,229 entitled "System and Method for Determining the Position of a Wireless CDMA Transceiver" and U.S. Patent No. 6,188,354, entitled "Method and Apparatus for Determining the Location of a Remote Station in a CDMA Communication Network."

The position locator 215 doesn't necessarily calculate the location of the data acquisition device 110 itself. It may receive the location from another device or application that performed the actual calculations. The position locator 215 can also do the calculations itself. As mentioned, the position locator 215 can reside in the data acquisition device 110 thereby enabling the data acquisition device to determine its location and send location information to the service manager 115.

[0061] The position locator 215 can determine the location of the data acquisition device 110 periodically, so that the location is being monitored on a regular basis. The position locator 215 can also determine the location upon the occurrence of certain events, such as when the user requests a location determination or when the user powers on the data acquisition device 110. The position locator 215 preferably communicates the location of the data acquisition device to the information manager 225.

[0062] In the next operation, the information manager 225 determines whether the data acquisition device 110 is near a qualified retail establishment using the location information provided by the position locator 215. This is represented by the decision box numbered 720. A "qualified retail establishment" is a retail establishment 120 that satisfies certain criteria, the criteria being specified in data that was provided by a user and that is stored in the central data store 230 or at the data acquisition device 110. In one embodiment, the criteria is specified in an items-needed list associated with the user's account, such as the lists is shown in Figures 4-6. The criteria corresponds to the information in the data slots of the list. For example, a first criteria can be whether the retail establishment stocks at least one of the items named in the list. Thus, if a retail establishment stocks an item on the list, the retail establishment satisfies the criteria and is therefore a qualified retail establishment.

[0063] There could also be other criteria, including whether the retail establishment 120 stocks an item that conforms to other user-specified requirements in the list, such as whether the item is within a specified price range, whether the item is actually in stock or whether a minimum quantity of the item is in stock. Another criteria can be the name of the retail establishment so that only retail establishments having a certain name can be classified as a qualified retail establishment. Other criteria may be accepted modes of payment or affiliations. With affiliations as criteria, the group of "qualified" retail establishments can be limited to those retail establishments that pay a fee to be a member

of an authorized criteria list, thereby limiting the establishments for which the user will receive notifications. The user can also specify as criteria a specific location or range of locations, so that only retail establishments at the specified location(s) can qualify. The information manager 225 classifies only those retail establishments that satisfy some or all of the specified criteria as a qualified retail establishment.

[0064] The information manager 225 can compile a list of qualified retail establishments by consulting data that is available in the data store 230. The information manager 225 can compare the criteria in the items-needed list of the user's account with available data on retail establishments 120 to determine if any retail establishments are qualified retail establishments. Based upon the comparison, those retail establishments that have data that meets the criteria are then added to the list of qualified retail establishments. As discussed above, a retail establishment 120 provides data to the information manager 225 regarding the items available at the retail establishment 120, as well as data that is descriptive of the name and location of the retail establishment.

[0065] With reference still to the operation shown in the decision box numbered 720, the information manager 225 compares the location of the data acquisition device 110 to known locations of qualified retail establishments to determine whether the data acquisition device is "near" the location of a qualified retail establishment. The data acquisition device 110 is "near" a qualified retail establishment when the location of the data acquisition device relative to the location of the qualified retail establishment satisfies a condition related to the relative locations of the qualified retail establishment and the data acquisition device 110. The condition can vary and could be specified by the user. For example, the condition can be that the distance between the two locations is less than a predetermined distance.

[0066] In one embodiment, the data acquisition device is near the location of a qualified retail establishment when the absolute location of the data acquisition device is within a predetermined distance of the absolute location of the qualified retail establishment. This is illustrated in Figure 8, which shows a qualified retail establishment 810 and a circle 820 that defines locations within a predetermined distance R from the qualified retail establishment 810.

[0067] The first data acquisition device 110a (shown in phantom lines) would qualify as being near the qualified retail establishment 810 because it is within the circle 820 and,



therefore, within the predetermined distance  $R$  of the qualified retail establishment 810. However, the second data acquisition device 110b does not qualify as being near the qualified retail establishment 810 because it is outside the circle 820 and, therefore, farther from the qualified retail establishment 810 than the predetermined distance.

5 [0068] Other conditions can also be used to determine whether the data acquisition device 110 is near a location, such as whether the data acquisition device 110 is on a common street as the location. The information manager 225 can take other factors into consideration, such as the location of known obstacles, such as hills and traffic signals, with respect to the user location.

10 [0069] If the information manager 225 determines that the data acquisition device is not near a qualified retail establishment, then a "No" outcome will result from the decision box numbered 720 of Figure 7. In such a case, the location of the data acquisition device 110 is preferably determined periodically for proximity to qualified retail establishments.

[0070] If the information manager 225 determines that the data acquisition device is  
15 indeed near a qualified retail establishment (a "Yes" outcome from the decision box 720), then the information manager 225 preferably causes an alarm to be sent to the data acquisition device 110 over the communication network 102. The alarm can be an active alarm, such as causing the data acquisition device to emit an audible notice, such as a beep. The alarm is preferably accompanied by a message that contains text, wherein the  
20 text notifies the user that he or she is near a retail establishment that provides an item on the list. Alternately, the alarm can be a notice that requests the user to call a message center or to check e-mail for further information.

[0071] The user can then visit the qualified retail establishment and obtain the item. Advantageously, once the user is at the retail establishment, the user can access an  
25 updated version of the items-need list in a variety of manners. The user can access the list on the data acquisition device 110 by causing the device to establish a link with the information manager 225 and download the updated list. The user can also access the list using the retail establishment communication device 150, if one is available. The retail establishment will preferably include a printer attached to the device 150, so the user can  
30 print out the list. When the item is obtained from the retail establishment, the user can then delete the item from the list using the data acquisition device 110 or device 150, which will then update the information manager 225 regarding any changes.

[0072] Figure 9 is a block diagram of an exemplary communication device 900 such as might comprise one or more of the nodes of the network 102, such as the service manager 115. The communication device 900 can include some or all of the components illustrated, as well as different versions of the components that are suited for the type of device. For example, if the communication device is a desktop computer, then it may include all of the components. However, if the communication device 900 is a mobile communication device then it may include only those components that are suited for a handheld device.

[0073] The communication device 900 operates at least partially under control of a central processor unit (CPU) 902. The CPU may be, for example, a "Pentium" microprocessor and associated integrated circuit chips, available from Intel Corporation of Santa Clara, California, USA. The CPU may also be a microprocessor that is configured for a handheld device such as a mobile phone or personal digital assistant. A user can input commands and data from data entry device, such as a keypad, keyboard and/or computer mouse 904. The user can view inputs and computer output at a display 906. The display can be, for example, a video monitor, flat panel display or liquid crystal display.

[0074] The communication device 900 can also include a direct access storage device (DASD) 908, such as a hard disk drive. The memory 910 typically comprises volatile semiconductor random access memory (RAM). The device 900 can includes a program product reader 912 that accepts a program product storage device 914, from which the program product reader can read data (and to which it can optionally write data). The program product reader can comprise, for example, a disk drive, and the program product storage device can comprise removable storage media such as a magnetic floppy disk, a CD-R disc, a CD-RW disc, or DVD disc.

[0075] The communication device 900 can communicate over a communication network 920 through a network interface 918 that enables communication over a connection 922 between the network 920 and the communication device 900. The network connection 922 can be wired or wireless. The network interface 918 typically comprises, for example, a Network Interface Card (NIC) that permits communications over a variety of networks. The network interface 918 can also include one or more antennas.

[0076] The CPU 902 operates under control of programming steps that are temporarily stored in the memory 910 of the communication device 900. When the programming steps are executed, the computer performs its functions. Thus, the programming steps implement the functionality of the processes described herein such as the functions of the service manager 115. The programming steps can be received from the DASD 908, through the program product storage device 914, or through the network connection 920. The program product storage drive 912 can receive a program product 914, read programming steps recorded thereon, and transfer the programming steps into the memory 910 for execution by the CPU 902. As noted above, the program product storage device can comprise any one of multiple removable media having recorded computer-readable instructions, including magnetic floppy disks and CD-ROM storage discs. Other suitable program product storage devices can include magnetic tape and semiconductor memory chips. In this way, the processing steps necessary for operation in accordance with the invention can be embodied on a program product.

[0077] Alternatively, the program steps can be received into the operating memory 910 over the network 920. In the network method, the computer receives data including program steps into the memory 910 through the network interface 918 after network communication has been established over the network connection 922 by well-known methods that will be understood by those skilled in the art without further explanation. The program steps are then executed by the CPU.

[0078] Any of the nodes of the computer network can have an alternative construction that supports the functionality described herein.

[0079] Figure 10 is a block diagram of an exemplary wireless device 1000 such as might comprise one or more of the nodes of the network 102, such as the data acquisition device 110 or communication device 135. The wireless device 100 includes an antenna 1002 that is configured to receive communication signals, such as from a GPS satellite or from a base station. The antenna communicates with a communication receiver 1010 that performs any necessary radio frequency processing, such as filtering, down converting, amplification, etc. Such radio frequency processing is well known to those of skill in the art.

[0080] The wireless device 1000 also includes a communication processor 1020 that communicates with the communication receiver 1010. The communication processor

1020 extracts from received signals information regarding the orbits of the satellites 130. Extraction of such information is well known to those of ordinary skill in the art. The information may be stored in memory 1040 of the wireless device 1000.

5 [0081] The wireless device 1000 also includes a position location receiver 1050 that is coupled to the antenna 1002. The position location receiver 1050 performs any front end radio frequency processing of position location signals received from a base station or satellite. The position location receiver 1050 is also coupled to a position location processor 1060 that determines the distance to satellites, according to methods that are well known to those of ordinary skill in the art. The position location processor 1060 also  
10 determines its own position using the locations of satellites.

[0082] The wireless device 1000 preferably also includes a display 1070 that is sized for a handheld device, and an interface 1080, such as a keypad. The display 1070 and interface 1080 allow a user to enter and view data.

[0083] The present invention has been described above in terms of a presently preferred  
15 embodiment so that an understanding of the present invention can be conveyed. There are, however, many configurations for the system not specifically described herein but with which the present invention is applicable. The present invention should therefore not be seen as limited to the particular embodiment described herein, but rather, it should be understood that the present invention has wide applicability with respect to  
20 information and communication systems generally. All modifications, variations, or equivalent arrangements and implementations that are within the scope of the attached claims should therefore be considered within the scope of the invention.

## CLAIMS

1. A method of managing information that is received from one or more users  
2 over a communication network in a communication environment, comprising:  
receiving information from a user at a first node of the communication network,  
4 the information indicating user-specified criteria related to an establishment located in the  
communication environment;  
6 storing the information at a central database that is linked to the communication  
network;  
8 monitoring the user's location within the communication environment;  
determining if the user is located near an establishment that satisfies one or more  
10 of the user-specified criteria; and  
sending a notification to the user if the user is near an establishment that satisfies  
12 one or more of the user-specified criteria.

2. A method as defined in claim 1, additionally comprising:  
2 receiving a revision to the information at a second node of the communication  
network;  
4 revising the information stored in the central database to reflect the revision to the  
information;  
6 making the information in the central database available to authorized users at a  
plurality of nodes of the communication network.

3. A method as defined in claim 1, wherein the first node of the  
2 communication network comprises a wireless data acquisition device.

4. A method as defined in claim 3, wherein the data acquisition device is a  
2 mobile phone.

5. A method as defined in claim 2, wherein the first node and the second  
2 node are the same device.

6. A method as defined in claim 1, wherein the received information includes  
2 a items needed list of at least one item, and wherein at least one criterion is whether an  
item on the list can be obtained at an establishment, and additionally comprising:  
4 sending a notification to a user only when the user is near an establishment at  
which the user can obtain an item on the items needed list.

7. A method as defined in claim 6, wherein an additional criterion describes a  
2 geographic location of an establishment, and additionally comprising:  
sending a notification to a user only when the user is near an establishment that is  
4 located at the geographic location described in the additional criterion.

8. A method as defined in claim 1, wherein monitoring the user's location  
2 within the communication environment comprises monitoring the location of a data  
acquisition device associated with the user, the data acquisition device comprising a node  
4 of the communication network.

9. A method as defined in claim 8, wherein the location of the data  
2 acquisition device is determined at the first node.

10. A method as defined in claim 9, wherein the location of the data  
2 acquisition device is determined by the data acquisition device.

11. A method as defined in claim 1, wherein the user is near an establishment  
2 when the location of the user is within a predetermined distance of the location of the  
establishment.

12. A method as defined in claim 1, wherein sending a notification to a user  
2 comprises sending a notification over the communication network to a data acquisition  
device associated with the user.

13. A method of managing data that is received from one or more users over a  
2 communication network in a communication environment, comprising:

receiving data from a node of the communication network, the data indicating at  
4 least one criterion that can be satisfied by an establishment located in the communication  
environment;

6 obtaining a location of a remote device in the communication environment,  
wherein the remote device is a node of the communication network;

8 identifying an establishment as a qualified establishment when an establishment  
satisfies at least one of the criterion;

- 10           determining whether the location of the remote device relative to the location of  
the qualified establishment satisfies a condition; and
- 12           transmitting an alarm over the communication network to the remote device if the  
condition is satisfied.

14.       A method as defined in claim 13, wherein the data includes a list of at least  
2       one item, and wherein one criterion is whether an item on the list can be obtained at an  
establishment such that an establishment can be qualified establishment only when an  
4       item on the list can be obtained at the establishment.

15.       A method as defined in claim 14, wherein an additional criterion relates to  
2       a price of an item on the list such that an establishment can be a qualified establishment  
only when an item on the list can be obtained at the establishment for a price specified in  
4       the data.

16.       A method as defined in claim 14, wherein an additional criterion relates to  
2       an establishment name such that an establishment can be a qualified establishment only  
when the establishment has the establishment name.

17.       A method as defined in claim 14, wherein an additional criterion describes  
2       a location such that an establishment can be a qualified establishment only when the  
establishment has a location that matches the location described in the criterion.



18. A method as defined in claim 13, wherein determining whether the  
2 location of the remote device relative to the location of the qualified establishment  
satisfies a condition comprises determining whether the location of the remote device is  
4 within a predetermined distance to the location of the qualified establishment.

19. A method as defined in claim 14, wherein transmitting an alarm over the  
2 communication network to the remote device comprises sending a notification to the  
remote device that an item from the list can be obtained at the qualified establishment.

20. A method as defined in claim 19, wherein transmitting an alarm over the  
2 communication network to the remote device additionally comprises sending a  
notification to the remote device indicating that the qualified establishment is nearby.

21. A method as defined in claim 13, additionally comprising:  
2 storing the data in a central data store on the communication network;  
receiving notification from a node of the communication network that the data has  
4 been revised;  
revising the data in the central data store to reflect the revised data; and  
6 making the data in the data store available for access by nodes of the  
communication network.

22. A method as defined in claim 13, additionally comprising making the data  
2 available only to a node that is operated by an authorized user.

23. A method as defined in claim 13, wherein the remote device comprises a  
2 mobile phone.

24. A method of managing data that is received from one or more users over a  
2 communication network in a communication environment, comprising:  
receiving data from a node of the communication network, the data including a list  
4 of items;  
obtaining a location of a user within the communication environment;  
6 identifying an establishment as a qualified establishment that provides at least one  
of the items on the list;  
8 determining that the location of the user relative to the location of the qualified  
establishment meets a standard; and  
10 notifying the user over the communication network that the user is near the  
qualified establishment.

25. A method as defined in claim 24, wherein the data includes at least one  
2 criterion and wherein an establishment is identified as a qualified establishment only  
when the establishment meets at least one of the criterion.

26. A method as defined in claim 25, wherein a criterion specifies a name of  
2 an establishment such that an establishment is identified as a qualified establishment only  
when the establishment has the specified name.

27. A method as defined in claim 25, wherein a criterion specifies the price of  
2 an item such that an establishment is identified as a qualified establishment only when the  
item can be obtained the establishment for the specified price.

28. A method as defined in claim 25, wherein a criterion specifies a location  
2 such that an establishment is identified as a qualified establishment only when the  
establishment is at the specified location.

29. A method as defined in claim 24, obtaining a location of a user within an  
2 environment comprises identifying a location of a remote device associated with the user.

30. A method as defined in claim 29, wherein notifying the user over a  
2 communication network that the user is near the qualified establishment comprises  
sending a transmission to the remote device, the transmission including a notice that the  
4 user is near the qualified establishment.

31. A method as defined in claim 29, wherein the remote device comprises a  
2 mobile phone.

32. A method as defined in claim 24, wherein determining that the location of  
2 the user relative to the location of the qualified establishment meets a standard comprises  
determining that the location of the user is within a predetermined distance of the location  
4 of the qualified establishment.

33. A method as defined in claim 24, additionally comprising maintaining a  
2 list of users that are authorized to access the data.

34. A system that manages information that is received from one or more users  
2 over a communication network in a communication environment, the system comprising  
one or more processors that execute program instructions and receive a data set, wherein  
4 the program instructions are executed to cause the processor to:

receive information from a user at a first node of the communication network, the  
6 information indicating user-specified criteria related to an establishment located in the  
communication environment;

8 store the information at a central database that is linked to the communication  
network;

10 monitor the user's location within the communication environment;

determine if the user is located near an establishment that satisfies one or more of  
12 the user-specified criteria; and

send a notification to the user if the user is near an establishment that satisfies one  
14 or more of the user-specified criteria.

35. A system as defined in claim 34, wherein the program instructions are  
2 executed to further cause the processor to:

receive a revision to the information at a second node of the communication  
4 network;

revise the information stored in the central database to reflect the revision to the  
6 information;

make the information in the central database available to authorized users at a  
8 plurality of nodes of the communication network.

36. A system as defined in claim 34, wherein the information includes a list of  
2 at least one item, and wherein one criterion is whether an item on the list can be obtained  
at an establishment, and wherein the program instructions are executed to further cause  
4 the processor to:

send a notification to a user only when the user is near an establishment at which  
6 the user can obtain an item on the list.

37. A system as defined in claim 34, wherein the user is near an establishment  
2 when the location of the user is within a predetermined distance of the location of the  
establishment.

38. A program product for use in a computer system that executes program  
2 steps recorded in a computer-readable media to perform a method for managing  
information that is received from one or more users over a communication network in a  
4 communication environment, the program product comprising:

a recordable media;

6 a program of computer-readable instructions executable by the computer system  
to perform operations comprising:

8 receiving information from a user at a first node of the communication network,  
the information indicating user-specified criteria related to an establishment located in the  
10 communication environment;

storing the information at a central database that is linked to the communication  
12 network;  
monitoring the user's location within the communication environment;  
14 determining if the user is located near an establishment that satisfies one or more  
of the user-specified criteria; and  
16 sending a notification to the user if the user is near an establishment that satisfies  
one or more of the user-specified criteria.

39. A program product as defined in claim 38, wherein the operations further  
2 comprise:  
receiving a revision to the information at a second node of the communication  
4 network;  
revising the information stored in the central database to reflect the revision to the  
6 information;  
making the information in the central database available to authorized users at a  
8 plurality of nodes of the communication network.

40. A program product as defined in claim 38, wherein the information  
2 includes a list of at least one item, and wherein one criterion is whether an item on the list  
can be obtained at an establishment, and wherein the operations further comprise:  
4 sending a notification to a user only when the user is near an establishment at  
which the user can obtain an item on the list.

41. A system that manages data that is received from one or more users over a  
2 communication network in a communication environment, the system comprising one or  
more processors that execute program instructions and receive a data set, wherein the  
4 program instructions are executed to cause the processor to:

receiving data from a node of the communication network, the data indicating at  
6 least one criterion that can be satisfied by an establishment located in the communication  
environment;

8 obtain a location of a remote device in the communication environment, wherein  
the remote device is a node of the communication network;

10 identify an establishment as a qualified establishment when an establishment  
satisfies at least one of the criterion;

12 determine whether the location of the remote device relative to the location of the  
qualified establishment satisfies a condition; and

14 transmit an alarm over the communication network to the remote device if the  
condition is satisfied.

42. A program product for use in a computer system that executes program  
2 steps recorded in a computer-readable media to perform a method for managing data that  
is received from one or more users over a communication network in a communication  
4 environment, the program product comprising:

a recordable media;

6 a program of computer-readable instructions executable by the computer system  
to perform operations comprising:

8 receiving data from a node of the communication network, the data indicating at  
least one criterion that can be satisfied by an establishment located in the communication  
10 environment;  
obtaining a location of a remote device in the communication environment,  
12 wherein the remote device is a node of the communication network;  
identifying an establishment as a qualified establishment when an establishment  
14 satisfies at least one of the criterion;  
determining whether the location of the remote device relative to the location of  
16 the qualified establishment satisfies a condition; and  
transmitting an alarm over the communication network to the remote device if the  
18 condition is satisfied.

43. A system that manages data that is received from one or more users over a  
2 communication network in a communication environment, the system comprising one or  
more processors that execute program instructions and receive a data set, wherein the  
4 program instructions are executed to cause the processor to:  
receive data from a node of the communication network, the data including a list  
6 of items;  
obtain a location of a user within the communication environment;  
8 identify an establishment as a qualified establishment that provides at least one of  
the items on the list;  
10 determine that the location of the user relative to the location of the qualified  
establishment meets a standard; and



12            notify the user over the communication network that the user is near the qualified  
establishment.

44.        A program product for use in a computer system that executes program  
2        steps recorded in a computer-readable media to perform a method for managing data that  
is received from one or more users over a communication network in a communication  
4        environment, the program product comprising:  
             a recordable media;  
6            a program of computer-readable instructions executable by the computer system  
to perform operations comprising:  
8            receiving data from a node of the communication network, the data including a list  
of items;  
10          obtaining a location of a user within the communication environment;  
             identifying an establishment as a qualified establishment that provides at least one  
12        of the items on the list;  
             determining that the location of the user relative to the location of the qualified  
14        establishment meets a standard; and  
             notifying the user over the communication network that the user is near the  
16        qualified establishment.

**WIRELESS COORDINATION AND MANAGEMENT SYSTEM****ABSTRACT OF THE DISCLOSURE**

5

[0084] The disclosed system manages information that is received from one or more users over a communication network. A user provides information to the network using a network node, such as a data acquisition device that is a wireless, mobile communication device. The system monitors the user's location within a communication environment and sends an alarm to a user when the user is near a location that satisfies user-specified criteria. The system stores the user-provided information at a central database that is linked to the communication network. When an authorized user revises the information, any other authorized user can access the revised information by accessing the central database through a node of the communication network.

15



100






Figure 1




Figure 2




Figure 3

410

Item	Quantity	Price	Retail Est. Name	Location
420				
420				
420				
420				

Figure 4

Item	Quantity	Retail Est. Name	Location

Figure 5

Item	Price	Retail Est. Name

Figure 6




Figure 7




Figure 8






Figure 9




Figure 10